



aegex10™ Intrinsicly safe tablet

Aegex Technologies provides intrinsically safe solutions for the world's most hazardous industrial operations in oil and gas, chemical, mining, pharmaceutical, public safety, utilities and other industries with explosive environments. Aegex solutions bring real-time connectivity to hazardous areas, helping organizations harness the power of data to optimize efficiency, safety and productivity.



Oil & Gas



Chemical



Biofuel



Pharmaceutical



Public Safety



Utilities

The **aegex10™ Intrinsicly Safe Tablet** is the most advanced, efficient, lightweight and rugged Windows tablet that is purpose-built for **Zone 1 / Division 1 hazardous areas**. Simple to deploy, it is the basis for an Industrial Internet of Things platform for hazardous industries, allowing operations to easily begin their digital transformation to Industry 4.0.

◆ Purpose-Built Intrinsicly Safe and Enterprise-Class Tablets:

Aegex devices are certified ATEX/IECEX Zone 1; certified by SGS to UL 913 Class I, II, III Division 1 Groups A-G; and IP65 for hazardous (classified) locations.

◆ Solutions for All Hazardous Zones and Jobs:

Aegex devices run the operating system and applications that allows for secure enterprise deployments.

◆ Enterprise Collaboration

Aegex devices use 4G LTE or Wi-Fi for real-time communications.



Certified ATEX/IECEX Zone 1

Certified by SGS to
UL 913 C I, II, III Div 1

10.1" WUXGA Display

Powered by Intel
Atom Quad Core

Windows 10



aegex.com



Intrinsically Safe Certifications	<p>UL913 5th edition: C, I, II, III Div 1 Gr A, G T4, T amb = -10°C...+50°C CI Z0 Gr IIC T4 IP65, T amb = -10°C...+50°C CAN/CSA-22.2 Part 157</p> <p>IECEX 60079-0 & -11: Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X Ex ib I Mb Ta = -10°C ...+50° ATEX 60079-0 & -11: II 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135°C Db IP6X II M2 Ex ib I Mb Ta = -10°C...+50° Dimensions:</p>
Exterior	<p>273 x 185 x 16.8 mm (10.75 x 7.28 x 0.66 in) Weight: 980 grams (2.16 lbs) IP65</p> <p>Screen: 10.1" AHVA Full HD Plus</p>
Display	<p>Resolution: 1920 x 1200 Capacitive touch: Multi-touch Contrast 800:1 Viewing angle (up/down, left/right) 170°</p> <p>Up to 12 hours of web browsing (Battery: 3.8V, 8700mAh,</p>
Battery Life	33Wh) Docking station: 0-90% in 2.5hours, to 100% in approx.
Charging time (in standby)	<p>3.5 hours USB charger: 0-90% in 4hours, to 100% in approx. 5.5 hours</p>
Storage/RAM	128GB storage / 4GB RAM
CPU Standard	<p>Intel® Quad-Core Atom processor 2.39GHz* Wi-Fi 802.11 a/b/g/n dual band Bluetooth® 4.0 Low Energy technology NFC Intel Wireless Display</p>
LTE Options (Standard +)	<p>LTE (North America): Sierra EM7355 - LTE: FDD Band 2,4,5,13,17,25 all bands with diversity - UMTS/HSPA+: Band 1,2,4,5,8, all bands with diversity - CDMA 1xRTT/EV-DO Rev A: BC0, BC1, BC10 - GSM/GPRS/EDGE: Quad-Band</p> <p>* LTE (EU, US, AU): Telit LN940A9 - LTE: Band 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 18, 19, 20, 21, 25, 26, 28, 29, 30, 38, 39, 40, 41, 66 - WCDMA: Band 1, 2, 3, 4, 5, 6, 8, 19 - GSM/GPRS/EDGE: N/A</p>
Location	<p>GPS / GLONASS (cold start <30s, warm start < 5s) Full-size USB 2.0</p>
Ports	<p>USB 3.0, Ethernet, and HDMI on system connector Micro USB for charging Charging pads (12V) microSDXC™ card slot (supports up to 2TB) Headset jack</p> <p>Windows 10 IoT Enterprise</p>
Software	<p>8.0 megapixel autofocus rear-facing camera with flash, full HD video 2.0 megapixel front-facing camera full HD video Front and rear microphones Stereo speakers</p> <p>Ambient light sensor, Accelerometer, Gyroscope, E-Compass, SAR proximity sensor</p>
Cameras, Video & Audio	
Sensors	
Security	<p>Silicon Level, Intel Security (SMEP, PPDRNG, fTPM, and TPM 2.0) Software Level Device Control BitLocker</p>
In the box	<p>aegex10™ intrinsically safe tablet Wall charger (power supply + USB cable)</p>

To request a demo or to talk to a product specialist, please contact our nearest office or go to:

www.aegex.com

UNITED STATES

Headquarters (Atlanta)

Phone: +1 (470) 242-4000

Email: contact@aegex.com

EUROPE

Sales (Netherlands)

Phone: +31 10 808 04 08

Email: contact@aegex.com

EUROPE

Sales (United Kingdom)

Phone: +44 141 846 0479

Email: contact@aegex.com

 [@aegextech](https://twitter.com/aegextech)

 contact@aegex.com



© 2021 Aegex Technologies, LLC. All Rights Reserved. The trademarks, logos, and service marks ("Marks") included herein are the property of Aegex Technologies, LLC or of their respective owners. AEGEX, AEGEX TECHNOLOGIES, aegex.com, and the Aegex logo are all trademarks of Aegex Technologies, LLC and/or its affiliates. Use of any Mark is not permitted without the prior written consent of Aegex Technologies, LLC or of the respective owner. The information in this document is subject to change without notice. Aegex and/or its representatives cannot be held responsible for any errors or inaccuracies within this document.

A10IS 12/21



Sr. Director of Rugged Tablet Sales

jgeary@decisionpt.com

978-490-7123

*Base Frequency 1.59 GHz, Burst Frequency 2.39 GHz

**Subject to verification of local carrier requirements

**P2P: ISO 18092, Reader/Writer: ISO 14443 -A-B, MIFARE, FeliCa®, ISO 15693, NFC Forum Tag Types

1 to 4 Card emulation: ISO 14443 -A-B-B', MIFARE, FeliCa RF, Distance up to 3 cm