



Model	DT362GL	DT362D Series	DT382GL	DT382DN
-------	---------	---------------	---------	---------

**System**

<b>CPU</b>	Intel® Pentium® Silver 4-Core, 1.1 GHz (up to 2.7 GHz)	Intel® N200, 4-core (up to 3.70 GHz) Intel® Core™ i3-N300, 8-core (up to 3.80 GHz)	Intel® Pentium® Silver 4-Core, 1.1 GHz (up to 2.7 GHz)	Intel® N200, 4-core (up to 3.70 GHz)
<b>RAM</b>	8GB	16GB	8GB	16GB
<b>Storage</b>	256GB flash	512GB to 1TB	256GB to 1TB	256GB to 1TB
<b>Operating System</b>	Microsoft® Windows® 10/11 IoT Enterprise	Microsoft® Windows® 11 IoT Enterprise	Microsoft® Windows® 10/11 IoT Enterprise	Microsoft® Windows® 11 IoT Enterprise
<b>NIST Compliance</b>	NIST Compliant BIOS Available			
<b>Display</b>	6" LED-Backlight (350 nits) screen with capacitive touch	6" LED-Backlit (850 nits) touchscreen	8" LED-Backlit, High-Brightness (800 nits) Touchscreen	8" LED-Backlit, High-Brightness (800 nits) Touchscreen
<b>Display Resolution</b>	720 x 1440	2160 x 1080 (2K)	1280 x 800	1280 x 800
<b>Fan/Fanless</b>	Fanless	Fanless	Fanless	Fanless
<b>Switches &amp; Buttons</b>	1 x Power Button, 2 x Trigger Buttons	1 x Power Button, 2 x Trigger Buttons	1 x Power Button, 2 x Trigger Buttons, 2 x Brightness Buttons, 4 x Programmable Buttons	1 x Power Button, 2 x Trigger Buttons, 2 x Brightness Buttons, 4 x Programmable Buttons
<b>Microphone</b>	N/A	Built-In Microphone	N/A	N/A
<b>Speaker</b>	N/A	Built-In Speaker	Built-In Speaker	Built-In Speaker

**Network Interface**

<b>WLAN</b>	Wi-Fi 802.11ac, 2.4/5 GHz Dual Band	Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band	Wi-Fi 802.11ac, 2.4/5 GHz Dual Band	Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band
<b>BT</b>	4.2 LE	5.3	4.2 LE	5.3

**I/O Ports**

<b>USB Port</b>	1 x USB Type-C (data transmitting and charging; data transmitting only available in one insertion direction)	1 x USB Type-C (data transmitting and charging; data transmitting only available in one insertion direction)	1 x USB 3.0, 1 x USB Type-C (data transmitting and charging)	1 x USB 3.0, 1 x USB Type-C (data transmitting and charging)
<b>Headset Jack</b>	N/A	N/A	1 (3.5 mm)	1 (3.5 mm)
<b>DC-In</b>	N/A	N/A	1	1
<b>Ethernet</b>	N/A	N/A	N/A	N/A
<b>SD Slot</b>	N/A	1 x Micro SD Card Slot	1 x Micro SD Card Slot	1 x Micro SD Card Slot
<b>Smart Card/CAC Reader</b>	Full Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card	Full Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card	N/A	N/A
<b>SIM Card Slot</b>	N/A	1 x Micro SD Card Slot (only DT362DN)	1 x NANO SIM Slot	1 x NANO SIM Slot

**Mechanical and Environmental**

<b>AC/DC Adapter</b>	Input: 100-240V AC; Output: 20V DC, 3.25A	Input: 100-240V AC; Output: 20V DC, 3.25A	Input: 100-240V AC; Output: 19V DC, 3.42A	Input: 100-240V AC; Output: 19V DC, 3.42A
<b>Battery Pack</b>	Hot-Swappable Battery (3300mAh)	Hot-Swappable Battery (2700mAh)	Hot-Swappable Battery (7.6V, 6000mAh) Hot-Swappable Battery (11.4V, 5400mAh) (Optional) Hot-Swappable Battery (11.4V, 8000mAh) (Optional)	Hot-Swappable Battery (7.6V, 6000mAh) Hot-Swappable Battery (11.4V, 5400mAh) (Optional) Hot-Swappable Battery (11.4V, 8000mAh) (Optional)
<b>Enclosure</b>	ABS + PC Plastic			
<b>Dimensions (H x W x D)</b>	7.6 x 3.7 x 1.2 in/192 x 95 x 31 mm	7.6 x 3.7 x 1.2 in/192 x 95 x 31 mm	5.8 x 9.2 x 1.1 in/147.3 x 234 x 27.7 mm	5.8 x 9.2 x 1.1 in/147.3 x 234 x 27.7 mm
<b>Weight</b>	1.1 lbs/485 g	1.1 lbs/485 g	3.43 lbs/1.1 kg	3.43 lbs/1.1 kg
<b>Durability</b>	IP65, MIL-STD-810H and MIL-STD-461G Certified, Class 1, Division 2, Groups A, B, C and D (Optional)	IP65, MIL-STD-810H and MIL-STD-461G Certified	IP65, MIL-STD-810H and MIL-STD-461G Certified	IP65, MIL-STD-810H and MIL-STD-461G Certified
<b>Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing</b>	Yes	Yes	Yes	Yes
<b>Regulatory</b>	FCC Class B, RoHS Compliant	FCC Class B, RoHS Compliant	FCC Class B, RoHS Compliant	FCC Class B, RoHS Compliant
<b>Temperature</b>	Operation: -10°C to 50°C (14°F to 122°F); Storage: -50°C ~ 70°C (-58°F ~ 158°F)			
<b>Humidity</b>	0% - 90% Non-Condensing			

**Major Options**

<b>Camera</b>	8MP Back Camera	5 MP Front USB Camera & 8 MP Back USB Camera	8 MP Back Camera with Auto Focus, White Balance, Gain Control, and Exposure Control	8 MP Back Camera with Auto Focus, White Balance, Gain Control, and Exposure Control
<b>Long Range Barcode Scanner</b>	Read range of 4 in (10cm) to 66 ft. (20.11m)	Read range of 4 in (10cm) to 66 ft. (20.11m)	N/A	N/A
<b>Barcode Scanner</b>	2D Barcode Scanner (Reads 1D & 2D)	2D Barcode Scanner (Reads 1D & 2D) Long Range 2D Barcode Scanner (up to 60ft)	2D Barcode Scanner (Reads 1D & 2D)	Long Range 2D Barcode Scanner (up to 60ft)
<b>GNSS Module</b>	GPS Module			
<b>NFC/RFID Reader</b>	HF 13.56 MHz, ISO 15693, 14443A(B), 18000-3 Mode 1			
<b>UHF RFID Reader</b>	865 – 928 MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; Reading Distance of 16 ft (4.87 m) with Integrated ThingMagic Micro Module & Embedded Antenna; Reading Range of 30 ft (9.1 m) with Trigger Grip Antenna		865 – 928 MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; Reading Distance of 16 ft (4.87 m) with Integrated ThingMagic Micro Module & Embedded Antenna; Reading Range of 30 ft (9.1 m) with Trigger Grip Antenna	
<b>Long-Range BT</b>	Class 1 BT (1000 ft)	N/A	Class 1 BT (1000 ft)	Class 1 BT (1000 ft)

\* Specifications subject to change without notice.



Model	DT 3 81R P	DT340T
-------	------------	--------

**System**

CPU RAM	Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5 GHz	Intel® Core™ i5-1340P, 12-Core, up to 4.6 GHz Intel® Core™ i7-1370P, 14-Core, up to 5.2 GHz
GPU	16GB	64GB
Storage Operating	N/A	NVIDIA RTX A1000 or RTX A2000 graphics card
System NIST	256GB to 1T SSD	256GB to 2TB Flash
Compliance Display	Microsoft® Windows® 10/11 IoT Enterprise Enterprise	Microsoft® Windows® 10/11 IoT Enterprise, 64bit or Ubuntu
Display Resolution	NIST Compliant BIOS Available	
Fan/Fanless	8" LED-Backlit, High-Brightness (800 nits) Touchscreen	14" LED-Backlit, High-Brightness (1,000 nits) Touchscreen with Multi-Touch
Switches & Buttons	1280 x 800	1920 x 1080
Microphone	Fanless	Fanless
Speaker	1 x Power Button, 2 x Brightness Buttons, 4 Programmable Buttons	1 x Power Button, 2 x Programmable Buttons
	N/A	Built-In Microphone with DSP for Real-Time Video Streaming
	Built-In Speaker	Built-In Speaker

**Network Interface**

WLAN	Wi-Fi 802.11ax, 2.4/5 GHz Dual Band	Wi-Fi 802.11ax 2.4/5/6 Ghz three band
BT	5.2	5.2

**I/O Ports**

USB Port	1 x USB 3.2 Gen 1 Type A, 1 x USB Type C	1 x USB 3.0, 2 x USB 2.0
Headset Jack	1 (3.5 mm)	1 (3.5 mm)
DC-In	1	1
Ethernet	1 x Ethernet 10/100/1000MB Base-T LAN	1 x Ethernet 10/100/1000MB Base-T LAN
SD Slot	1 x Micro SD Card Slot	N/A
Smart Card/CAC Reader	Full Slot (reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card	Full-Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card
SIM Card Slot	N/A	

**Mechanical and Environmental**

AC/DC Adapter	Input: 100-240V AC; Output: 19V DC, 3.25A	Input: 100-240V AC; Output: 19V 65W for w/o GPU SKU and 19V 120W for A1000 SKU
Battery Pack	Hot-Swappable Battery (7.6V, 6000mAh) Optional: Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh)	Input: 100-240V AC; Output: 19V 65W for w/o GPU SKU and 19V 230W for A1000 SKU
Enclosure	ABS + PC Plastic	ABS + PC Plastic and Magnesium-Aluminum Alloy
Dimensions (H x W x D)	5.8 x 9.2 x 1.0 in/147.3 x 234 x 25.5 mm	9.6 x 14.8 x 1.16 in/244 x 376 x 29.5 mm
Weight	2.65 lbs/1.2 kg	6.38 lbs/2.9 kg
Durability	IP65, MIL-STD-810H and MIL-STD-461G Certified	IP65, MIL-STD-810H and MIL-STD-461G Certified
Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing	Yes	Yes
Regulatory	FCC Class B, CE, RoHS, Energy Star 8.0 Compliant	FCC Class B, CE, RoHS, Energy Star 8.0 Compliant
Temperature	Operation: AC Mode: -20°C to 45°C (-4°F to 113°F) Battery Mode: 0°C to 40°C (32°F to 104°F) Optional Wider Operating Temperature Range: -30°C to 40°C (-22°F to 104°F) Storage: -50°C ~ 70°C (-58°F ~ 158°F)	Operation*: -20°C ~ 60°C (-4°F ~ 140°F); tested under MIL-STD-810H method 501.7, Procedure II, and method 502.7, Procedure II *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C ~ 50°C (32°F ~ 122°F) Storage: -50°C ~ 70°C (-58°F ~ 158°F)
Humidity		

**Major Options**

Camera	8 MP Front and Back Cameras w/ Auto Focus, White Balance, Gain Control, and Exposure Control	8M Back Camera with Flash
Long Range Barcode Scanner	N/A	N/A
Barcode Scanner	N/A	N/A
GNSS Module	GPS Module	
NFC/RFID Reader	N/A	N/A
UHF RFID Reader	N/A	N/A
Mobile Broadband	4G LTE/AWS	4G LTE/AWS
Long-Range BT	Class 1 BT (1000 ft)	N/A
ANTENNA	N/A	Dual pass through antennas integrated in the docking cradle
GPU	N/A	Integrated graphics card, NVIDIA RTX A1000 or RTX A2000

\* Specifications subject to change without notice.



Model	DT302RP	DT312RP	DT323RP
-------	---------	---------	---------

## System

<b>CPU</b>	Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ U300, 5-Core, up to 4.4 GHz	Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz	Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz
<b>RAM</b>	8GB to 32GB	8GB	8GB
<b>Storage</b>	256GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover	512GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover	512GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover
<b>Operating System</b>	Microsoft® Windows® 10/11 IoT Enterprise	Microsoft® Windows® 11 IoT Enterprise	Microsoft® Windows® 11 IoT Enterprise
<b>NIST Compliance</b>	NIST Compliant BIOS Available		NIST Compliant BIOS Available
<b>Display</b>	10.1" LED-Backlit, Sunlight Readable (800 nits) Touchscreen LCD	11.6" LED-Backlit, Sunlight Readable (1000 nits) Touchscreen	13.3" LED-Backlit, Sunlight Readable (1000 nits) Touchscreen
<b>Display Resolution</b>	1920 x 1200	1920 x 1200	1920 x 1080
<b>Fan/Fanless</b>	Fanless	Fanless	Fanless
<b>Switches &amp; Buttons</b>	1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons	1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons	1 x Power Button; 2 x Brightness Buttons; 5 x Programmable Buttons
<b>Microphone</b>	Built-In Microphone	Built-In Microphone with DSP for Real-Time Video Streaming	Built-In Microphone
<b>Speaker</b>	Built-In Speaker	Built-In Speaker	Built-In Speaker
<b>Camera</b>	5 MP Front Camera & 8 MP Back Camera (Options)	5 MP Front Camera & 8 MP Back Camera (Options)	5 MP Front Camera & 8 MP Back Camera (Options)

## Network Interface

<b>WLAN</b>	Wi-Fi 802.11ax 2.4/5/6 Ghz three band	Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band	Wi-Fi 802.11ax, 2.4/5/6 GHz Three Band
<b>BT</b>	5.2	5.2	5.3

## I/O Ports

<b>USB Port</b>	1 x USB 3.0, 1 x USB Type-C (Data transmission & Power Charging)	1 x USB 3.0, 1 x USB Type-C	1 x USB 3.0, 1 x USB Type-C
<b>Headset Jack</b>	1 (3.5 mm)	1 (3.5 mm)	1 (3.5 mm)
<b>DC-In</b>	1	1	1
<b>Ethernet</b>	1 x Ethernet 10/100/1000MB Base-T LAN	1 x Ethernet 10/100/1000MB Base-T LAN	1 x Ethernet 10/100/1000MB Base-T LAN
<b>SD Slot</b>	1 x Micro SD Card Slot	N/A	N/A
<b>Smart Card/CAC Reader</b>	N/A	N/A	N/A

## Mechanical and Environmental

<b>AC/DC Adapter</b>	Input: 100 – 240V AC; Output: 19V DC, 3.42A	Input: 100-240V AC; Output: 19V DC, 3.42A	Input: 100-240V AC; Output: 19V DC, 3.42A
<b>Battery Pack</b>	Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh)	Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh)	Hot-Swappable Battery (11.4V, 3800mAh) (Optional) 60W Hot-Swappable Battery (11.4V, 5400mAh) (Optional) 90W Hot-Swappable Battery, (11.4V, 8000mAh)
<b>Enclosure</b>	ABS + PC Plastic and Magnesium-Aluminum Alloy	ABS + PC Plastic and Magnesium-Aluminum Alloy	ABS + PC Plastic and Magnesium-Aluminum Alloy
<b>Dimensions (H x W x D)</b>	7.7 x 10.71 x 0.79 in/195.6 x 272 x 20 mm	8.3 x 12.4 x 0.78 in/212 x 316 x 20 mm	12.8 x 10.7 x 0.8 in/325 x 273.5 x 20 mm
<b>Weight</b>	3 lbs/1.32 kg	3.43 lbs/1.55 kg	3.81 lbs/1.72 kg
<b>Durability</b>	IP65, MIL-STD-810H and MIL-STD-461G Certified	IP65, MIL-STD-810H and MIL-STD-461G Certified	IP65, MIL-STD-810H and MIL-STD-461G Certified
<b>Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing</b>	Yes	Yes	Yes
<b>Regulatory</b>	CE, FCC Class B, RoHS, Energy Star 8.0 Compliant	FCC Class B, CE, RoHS Compliant	FCC Class B, CE, RoHS Compliant
<b>Temperature</b>	Operation: -10°C ~ 60°C (14°F ~ 140°F); *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C ~ 50°C (32°F ~ 122°F) *When using DT302 with AC power adapter, to comply with safety regulation, the recommended usage temperature is from 0°C to 40°C Storage: -50°C ~ 70°C (-58°F ~ 158°F)	Operation*: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C ~ 50°C (32°F ~ 122°F)	Operation*: -10°C to 60°C (14°F to 140°F) Optional -30°C to 60°C (-22°F to 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C ~ 50°C (32°F ~ 122°F)
<b>Humidity</b>	0% - 90% Non-Condensing	0% - 90% Non-Condensing	0% - 90% Non-Condensing

## Major Options

<b>Camera</b>	5 MP Front Camera & 8 MP Back Camera	5MP Front Camera & 8MP Back Camera	5 MP Front Camera & 8 MP Back Camera
<b>Barcode Scanner</b>	2D Barcode Scanner (Reads 1D & 2D)	2D Barcode Scanner (Reads 1D & 2D)	2D Barcode Scanner (Reads 1D & 2D)
<b>GNSS Module</b>	U-blox M9N GNSS Module	U-blox M9N GNSS Module	GPS Module with Concurrent Reception of GPS and GLONASS; Industry Leading - 167dBm Navigation Sensitivity
<b>Mobile Broadband</b>	4G/5G	4G LTE/AWS	4G/5G

\* Specifications subject to change without notice.

# Rugged Tablets



Model	DT 3 01Y	DT301YR	DT311YR
<b>System</b>			
CPU	Intel® Pentium® Gold 7505, 2-Core, up to 3.5 GHz	Intel® Core™ i7-1355U, 10-Core, up to 5.0 GHz Intel® Core™ i5-1335U, 10-Core, up to 4.6 GHz	
RAM	8GB to 32GB	8GB to 32GB	
Storage	256GB to 2TB Flash	256GB to 2TB Flash	256GB to 2TB Flash *Support quick access SSD function to easily replace the SSD without opening the back cover
Operating System	Microsoft® Windows® 10/11 IoT Enterprise	Microsoft® Windows® 10/11 IoT Enterprise	
NIST Compliance	NIST Compliant BIOS Available		
Display	10.1" LED-Backlit, High-Brightness (1000 nits) Touchscreen	10.1" LED-Backlit, High-Brightness (1000 nits) Touchscreen	11.6" LED-Backlit, High-Brightness (1000 nits) Touchscreen
Display Resolution	1920 x 1200	1920 x 1200	1920 x 1080
Fan/Fanless	Fanless		
Switches & Buttons	1 x Power Button, 2 x Brightness Buttons, 5 x Programmable Buttons	1 x Power Button; 2 x Brightness Buttons; 5 x Programmable Buttons	
Microphone	Built-In Microphone		
Speaker	Built-In Speaker		

## Network Interface

WLAN	Wi-Fi 802.11ax, 2.4/5 GHz Dual Band	Wi-Fi 802.11ax, 2.4/5 GHz Dual Band
BT	5.2	

## I/O Ports

USB Port	1 x USB 3.0, 1 x USB Type-C	1 x USB 3.0, 1 x USB Type-C
Headset Jack	1 (3.5 mm)	1 (3.5 mm)
DC-In	1	1
Ethernet	1	1 x Ethernet 10/100/1000MB Base-T LAN
Smart Card/CAC Reader	Full Slot (reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card	Full-Slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V Smart Card

## Mechanical and Environmental

AC/DC Adapter	Input: 100-240V AC; Output: 19V DC, 3.42A	Input: 100 – 240V AC; Output: 19V DC, 3.42A	Input: 100 – 240V AC; Output: 20V DC, 3.25A
Battery Pack	Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh) (Optional)	Hot-Swappable Battery (11.4V, 5400mAh) Hot-Swappable Battery (11.4V, 8000mAh)(Optional)	
Enclosure	ABS + PC Plastic and Magnesium-Aluminum Alloy		
Dimensions (H x W x D)	7.8 x 11 x 0.86 in/198 x 280 x 21.9 mm	7.8 x 11 x 0.86 in/198 x 280 x 21.9 mm	8.3 x 12.4 x 0.86 in/212 x 316 x 21.9 mm
Weight	3.1 lbs/1.4 kg	3.1 lbs/1.4 kg	3.5 lbs/1.6 kg
Durability	IP65, MIL-STD-810H and MIL-STD-461G Certified	IP65, MIL-STD-810H and MIL-STD-461G Certified	
Hazard of Electromagnetic Radiation to Ordnance (HERO) Testing	Yes	Yes	Yes
Regulatory	FCC Class B, CE, RoHS, Energy Star 8.0 Compliant		
Temperature	Operation: -10°C ~ 60°C (14°F ~ 140°F) Optional -30°C ~ 60°C (-22°F ~ 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C ~ 50°C (32°F ~ 122°F) Storage: -50°C ~ 70°C (-58°F ~ 158°F)	Operation: -10°C ~ 60°C (14°F ~ 140°F) Optional -30°C ~ 60°C (-22°F ~ 140°F) *For battery optimal functionality and performance, the recommended usage temperature range is from 0°C ~ 50°C (32°F ~ 122°F) Storage: -50°C ~ 70°C (-58°F ~ 158°F)	
Humidity	0% - 90% Non-Condensing		

## Major Options

Camera	2MP Front Camera & 8MP Back Camera	2MP Front Camera & 8MP Back Camera
Barcode Scanner	2D Barcode Scanner (Reads 1D & 2D)	2D Barcode Scanner (Reads 1D & 2D)
GNSS Module	U-blox M9N GNSS Module	
UHF RFID Reader	865 – 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 30 ft (9.14m) Reading Distance	865 – 928MHz, EPCglobal Class 1 Gen 2/ISO 18000-6C; 30 ft (9.14m) Reading Distance
Mobile Broadband	4G LTE/AWS	4G LTE/AWS
Long-Range BT	Class 1 BT (1000 ft)	Class 1 BT (1000 ft)

\* Specifications subject to change without notice.



John Geary  
Sr. Dir. Rugged Tablet Sales  
Barcoding + DecisionPoint Systems  
M 978-490-7123  
E jgeary@decisionpt.com

